

Lake Greenwood Continuous Monitoring Study Periodic Report

July 22, 2020 - October 7, 2020


This study funded through a joint effort consisting of Greenwood County Lake Management (GCLM), Laurens County Water and Sewer Commission (LCWSC), City of Greenville, and Renewable Water Resources (ReWa).



Continuous Monitoring Report Lake Greenwood at Reedy Arm




July 22, 2020 -- October 7, 2020





MONITORING LOCATION CHARACTERISTICS		
Station Location Name	Reedy Arm	
Latitude	34.347141 °N	
Longitude	82.109702 °W	
Appoximate Drainage Area	260 square miles	


RAINFALL CHARACTERISTICS Data collected at rain gauge located at Ekom Beach Road crossing of Reedy River			
Number of Storms Over 0.1 in"	12		
Max Storm Rainfall	2.62 in		
Total Rainfall for Period (Length of deployment: 11 weeks)	11.46 in		


CONTINUOUS WATER	SUMMARY STATISTICS					
QUALITY PARAMETERS:	MIN	MAX	MEDIAN	MEAN	ST. DEV.	
Turbidity (NTU):	3	49	10	11	6	
Sp. Conductivity (uS/cm):	66	149	102	105	17	
Dissolved Oxygen (mg/L):	5.4	14.6	8.6	8.7	1.2	
pH:	6.7	9.3	7.5	7.6	0.5	
Chlorophyll* (ug/L)	0.01	45	3	4	4	
Temperature (°F):	66	92	84	81	7	
















Continuous Monitoring Report Lake Greenwood at Reedy Arm



July 22, 2020 -- October 7, 2020

Explanation of Statistics:		
The minimum value recorded by the datasonde during the reporting period.		
The maximum value recorded by the datasonde during the reporting period.		
The median value represents the 50th percentile of the distribution of all values recorded during the reporting period. Half of the		
recorded values during this period fell above the median value and half fell below this value.		
The average of all the 15-minute values recorded by the datasonde during this reporting period.		
The standard deviation is a measure of the variation within a dataset. A large standard deviation indicates significant variability in the dataset and a small standard deviation represents low variability.		

	D	iscrete Sami	ale Results (`allected to	n Date		
Discrete Sample Results Collected to Date Analyzed by Pace Analytical and ETT Environmental Laboratories							
Sample Date	Collected By	TSS mg/L	TN mg/L	TKN mg/L	NO3+NO2 mg/L	TP mg/L	Chl-a ug/L
*9/11/2018 13:30	CPW		1.10			0.110	30.8
9/26/2018 9:10	GCLM	9.6	0.88	0.51	0.37	0.091	24.5
11/7/2018 7:40	GCLM	11.5	1.9	ND	1.4	0.054	2.7
11/19/2018 9:30	GCLM	27.4	1.2	ND	0.87	0.12	21.1
11/28/2018 9:20	GCLM	10.7	1.5	ND	1.3	0.093	4
3/27/2019 9:12	GCLM	7.8	1.5	ND	1.1	ND	5.4
5/22/2019 9:07	GCLM	3.6	1.00	0.52	0.49	ND	6.7
5/29/2019 8:41	GCLM	9.7	1.37	0.67	0.7	ND	20.7
6/19/2019 8:49	GCLM	3	0.94	ND	0.44	ND	10.7
6/26/2019 8:40	GCLM	ND	1.4	ND	0.96	ND	4.6
7/10/2019 8:55	GCLM	7.3	1.4	0.54	0.89	ND	11.7
7/24/2019 8:40	GCLM	5.1	1.3	0.69	0.57	ND	10.7
8/14/2019 8:36	GCLM	2.9	1.1	0.63	0.48	ND	9.3
8/28/2019 8:40	GCLM	3.8	1.1	ND	0.66	ND	21.2
9/11/2019 8:30	GCLM	8.1	0.97	0.65	0.32	ND	17.9
4/22/2020 8:45	GCLM	8.3	1.4	0.4	1	0.048	2
5/27/2020 8:20	GCLM	17.9	1.2	0.56	0.61	0.081	2
6/17/2020 8:20	GCLM	33.3	1.3	0.57	0.78	0.05	
7/15/2020 8:30	GCLM	3.4	1.2	0.6	0.56	0.027	
7/29/2020 8:30	GCLM	5.3	1.3	0.62	0.68	ND	6
8/19/2020 8:45	GCLM	ND	1.2	0.72	0.49	0.038	2
9/24/2020 9:00	GCLM	6.77	0.989	0.44	0.549	0.092	21.3

^{*}Samples collected by Greenwood Commissioners of Public Works (CPW) are analyzed for TN, TP, and Chl-a only.

These samples are collected in order to provide information on parameters which cannot be reliably measured in-situ. These sample results may be used in the future to develop statistical relationships with continuously monitored parameters in an effort to estimate continuous concentrations of these parameters. A sufficient sample size for regression analysis is typically 20 samples or more collected across a range of weather conditions.

Definitions			
Chl-a	Chlorophyll-a		
ND	Non Detected at the Reporting Limit		
NO3+NO2	Nitrate + Nitrite as Nitrogen		
TKN	Total Kjeldahl Nitrogen		
TN	Total Nitrogen		
TP	Total Phosphorus		
TSS	Total Suspended Solids		